



Foamy One Step

Foamy One Step can be used as an alkaline presoak or a rocker panel cleaner.

Dilution

Dilution rates range from 17 to 48:1 with water for use as an alkaline presoak or rocker panel cleaner.

Application

High pH (alkaline) Presoak

- Used in Tunnels
- Used in In-Bays-Automatics (Soft Touch or Touch Free)
- Used in Self-Serve

Technical Data

Appearance: Clear Amber Liquid

Odor: Mild Alkali Foaming: High pH: 14.0

Rinsing: Complete Stability: Good

Wetting Ability: Excellent

Storage Instructions

Wear all appropriate Personal Protective Equipment (PPE). Wear respiratory protection or ensure adequate ventilation at all times as vapors can accumulate in confined or poorly ventilated areas. Avoid aerosolizing product. Use the product in a manner which minimizes splashes and/or the creation of dust. Keep containers closed when not in use. Store at room temperatures, i.e., 40 to 95 F (4 to 35 C). Do not allow concentrated product to come in contact with aluminum. Product may become unstable if cooled below 40°F. Keep product warm and above bare concrete floors. If product becomes unstable, add hot water and mix well. Product can be used if thawed properly. Store in a cool location. Provide ventilation for receptacles. Store away from foodstuffs. Do not store together with acids. Store in cool, dry conditions in well sealed receptacles. Keep container tightly sealed.

Product Code

CW776

Safety


Hazard statements: Causes severe skin burns and eye damage. Causes serious eye damage

Signal Word: DANGER



Precautionary statements: Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands and exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Immediately call a POISON CENTER or doctor/physician. Specific treatment (see First Aid on this label or consult on this SDS). Wash contaminated clothing before reuse. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

National Fire Protection Association (NFPA):



Shipping

UN3266, Corrosive liquid, basic, inorganic, n.o.s. (Potassium hydroxide) 8, PG III